

Large Diameter Couplings OD842 - 2038

Specifications

Pipe OD (mm)	Pipe Material	Working Pressure (bar)	Gasket Mould No.	Tolerance (mm) on Pipe OD for Distance L		Coupling Section Type		Bolts No. x Dia	Weight (kg)		Diameter A (mm)
				+	-	Standard Sleeve	Long Sleeve		Standard Sleeve	Long Sleeve	
842	Ductile Iron	18.9	J65LS	1.0	4.5	L02	L03	14 x M12	44.6	60.3	931
842	Ductile Iron	25.0	J65LS	1.0	4.5	YF2	YF3	12 x M16	78.7	93.6	950
842	Ductile Iron	29.1	J116M	1.0	4.5	A2E	A2H	14 x M16	103.4	122.7	965
864	Steel	17.9	J66LS	1.6	1.6	L02	L03	14 x M12	45.7	61.8	955
864	Steel	28.4	J116M	1.6	1.6	A2E	A2H	14 x M16	105.9	125.8	988
867	Coated Steel	17.8	J66LS	1.6	1.6	L02	L03	14 x M12	45.9	62.0	958
867	Coated Steel	28.2	J117M	1.6	1.6	A2E	A2H	14 x M16	106.3	126.2	992
914	Steel	16.0	J67LS	1.6	1.6	L02	L03	14 x M12	48.2	65.1	1005
914	Steel	26.8	J117M	1.6	1.6	A2E	A2H	14 x M16	111.6	132.4	1039
916	Coated Steel	16.0	J67LS	1.6	1.6	L02	L03	14 x M12	48.3	65.2	1007
916	Coated Steel	26.8	J117M	1.6	1.6	A2E	A2H	14 x M16	111.8	132.7	1041
945	Ductile Iron	22.0	J70LS	1.0	5.0	YF2	YF3	12 x M16	87.5	104.0	1054
945	Ductile Iron	25.9	J118M	1.0	5.0	A2E	A2H	14 x M16	115.0	136.5	1069
1016	Steel	19.6	J71LS	1.6	1.6	YF2	YF3	14 x M16	94.3	112.2	1125
1019	Coated Steel	19.4	J71LS	1.6	1.6	YF2	YF3	14 x M16	94.6	112.5	1129
1048	Ductile Iron	18.4	J71LS	1.0	5.0	YF2	YF3	14 x M16	96.9	115.3	1156
1048	Ductile Iron	26.8	J119M	1.0	5.0	A2E	A2H	16 x M16	127.1	151.0	1171
1067	Steel	17.7	J72LS	1.6	1.6	YF2	YF3	14 x M16	98.6	117.3	1177
1067	Steel	26.3	J119M	1.6	1.6	A2E	A2H	16 x M16	129.4	153.7	1192
1070	Coated Steel	17.6	J72LS	1.6	1.6	YF2	YF3	14 x M16	98.9	117.6	1180
1070	Coated Steel	26.2	J120M	1.6	1.6	A2E	A2H	16 x M16	129.7	154.1	1195
1118	Steel	16.2	J73LS	1.6	1.6	YF2	YF3	14 x M16	102.9	122.4	1227
1121	Coated Steel	16.0	J73LS	1.6	1.6	YF2	YF3	14 x M16	103.2	122.8	1231
1152	Ductile Iron	24.4	J121M	1.0	6.0	A2E	A2H	16 x M16	138.7	164.7	1275
1219	Steel	23.0	J121M	1.6	1.6	A2E	A2H	16 x M16	146.3	173.7	1343
1222	Coated Steel	23.0	J121M	1.6	1.6	A2E	A2H	16 x M16	146.6	174.1	1347
1255	Ductile Iron	25.2	J122M	1.0	6.0	A2E	A2H	18 x M16	151.0	179.4	1378
1422	Steel	24.5	J125M	1.6	3.0	A2E	A2H	20 x M16	170.5	202.6	1546
1426	Coated Steel	24.4	J125M	1.6	3.0	A2E	A2H	20 x M16	171.0	203.1	1551
1462	Ductile Iron	23.8	J125M	1.0	7.0	A2E	A2H	20 x M16	174.8	207.7	1585
1620	Steel	20.3	J127M	3.0	3.0	A2E	A2H	24 x M16	192.4	230.9	1745
1626	Coated Steel	20.2	J127M	3.0	3.0	A2E	A2H	24 x M16	194.2	231.7	1751
1668	Ductile Iron	19.2	J128M	1.0	7.0	A2E	A2H	24 x M16	199.4	237.0	1791
1829	Steel	16.0	J130M	3.0	3.0	A2E	A2H	24 x M16	217.5	258.5	1954
1835	Coated Steel	24.0	J184H	3.0	3.0	XSXG	-	32 x M16	378.4	-	1970
2032	Steel	22.1	J186H	3.0	3.0	XSXG	-	36 x M16	418.6	-	2167
2038	Coated Steel	22.0	J186H	3.0	3.0	XSXG	-	36 x M16	419.7	-	2173

Materials & Relevant Standards

Centre Sleeve/End Rings

Steel to BS EN10025-2: Grade S275JR

Bolts/Nuts/Washers

Bolts - Steel to BS EN ISO898-1: Property Class 4.8

Nuts - Steel to BS4190: Grade 4

Washers - Stainless Steel to BS1449:Part 2: Grade 304S15

Coatings

Body, Flange & End Ring - Rilsan Nylon 11 to WIS 4-52-01 Part 1

Nuts and Bolts - Sheraplex coated to WIS 4-52-03

Gaskets: L02/L03/YF2/YF3

Rubber 80 IRHD Moulded Compound to BS EN681-1:

Type WA,WC,WG or BS EN682: Type G

(other materials available on request)

Gaskets: A2E/A2H/XSXG

Rubber 70 IRHD Moulded Compound to BS EN681-1: Type WA, WC, WG or BS EN682: Type G (other materials available on request)

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.