



ALL PRODUCT DIMENSIONS ARE BEFORE COATING

REFERENCE DRAWING ONLY - NOT TO BE USED FOR INSPECTION PURPOSES

DO NOT SCALE

MATERIAL SPECIFICATION
END RING (Part 1) STEEL to BS EN10025-2 GRADE S275JR CENTRE SLEEVE (Part 2) STEEL to BS EN10025-2 GRADE S275JR GASKET (Part 3) RUBBER 80 HARDNESS Grade to suit service BOLTS (Part 4) STEEL BS EN ISO898-1 PROPERTY CLASS 4.8 NUTS (Part 5) STEEL BS4190 GRADE 4 WASHERS (Part 6) STAINLESS STEEL BS1449:PART 2 GRADE 304S15
FINISH SPECIFICATION
NOTES
Locating Plugs/Pin Register If Locating Plugs/Pins are required, 3 are to be supplied.
BOLT TORQUES
Torque to 95-120Nm



ISOMETRIC VIEW

PIPE O.D.	PIPE MATERIAL	PIPE TOLERANCE		BOLTS	GASKET MOULD	WORKING PRESSURE	TEST PRESSURE	WEIGHT KG	ASSEMBLY DRG NO
		+	-						
1121.00	STEEL	1.60	1.60	14-M16x265	J73LS	16.0bar	24.1bar	103.19	7879_908

OVERALL DIMENSIONS DRAWING
FOR REFERENCE ONLY
VIKING JOHNSON RESERVE THE
RIGHT TO AMEND DETAILS WITHOUT
PRIOR NOTIFICATION

This drawing is the exclusive property of VIKING JOHNSON and is confidential and must not be reproduced or disclosed to a third party without written consent. It must be used only for the purpose which it has been issued and is returnable on request.

CRANE A Crane Co Company

OVERALL DIMENSIONS OF
VIKING JOHNSON COUPLING ASSEMBLY
'YF2' SECTION
FOR 1121.00mm O.D. PIPE

RELEASE LEVEL: Released

SHEET 1 OF 1



DRAWN	AUTO	SCALE	1:250
DATE	07/12/18	GENERIC	7879

DRG NO SKP1551-1