 DO NOT SCALE

END RING (Part 1)  
Ductile Iron to BS EN1563  
SYMBOL EN-GJS-450-10

CENTRE SLEEVE (Part 2)  
Ductile Iron to BS EN1563  
SYMBOL EN-GJS-450-10


GASKET (Part 3)  
70 & 80 IRHD EPDM to BS EN681-1 or  
70 & 80 IRHD Nitrile to BS2494

INSERT (Part 4)  
Stainless Steel to BS3146  
Grade ANC2

BOLT (Part 5)  
Steel to BS EN ISO898-1  
Property Class 8.8

NUT (Part 6)  
Steel to BS EN29898-2  
Grade 8.0

WASHER (Part 7)  
Stainless Steel to BS1449:Part 2  
Grade 304S15



PIPE O.D.	TOLERANCE ON O.D.	BOLTS	GASKET MOULD	INSERT	WEIGHT KG	PRESSURE (bar)		ASSEMBLY DRG NO
		No-ØxLEN		NOxTYPE		WORKING	TEST	
118	+2.2 -3.0	4-M12x195	1618	4 x E	5.6	16	24	7935/2

This drawing is the exclusive property of VIKING JOHNSON and is confidential and must not be reproduced or disclosed to a third party without written consent. It must be used only for the purpose which it has been issued and is returnable on request.

©

## OVERALL DIMENSIONS OF FLEXLOCK COUPLING FOR FOR 118mm O.D. PIPE

